



Trimble Forensics GNSS Solution



KEY FEATURES

- ▶ Trimble® Forensics Capture supports GNSS based workflows.
- ▶ Designed to specifically work with the Trimble R4sLE receiver, or any R-series receivers.
- ▶ Built-in ground scaling and local coordinate system for every scene. No need for site calibrations.
- ▶ GNSS and SX10 or total station integrated surveying workflows.
- ▶ All collected data is stored within the same Capture file, regardless of using GNSS or total stations or SX10.
- ▶ Trimble R4sLE is waterproof, impact resistant and rated for -40°C to $+65^{\circ}\text{C}$. Extremes in temperature are not a problem.

Learn more:

<https://forensics.trimble.com/gnss-solution>

GNSS CHARACTERISTICS¹

- 240 GNSS channels
 - GPS L1C/A, L1P(Y), L2P(Y), L2C
 - GLONASS L1C/A, L2C/A, L3
 - BeiDou B1 (phase 2), B2
 - Galileo E1, E5b
 - QZSS L1C/A, L2C, L1SAIF
 - SBAS L1C/A
 - L-band
- Support for Trimble RTX™ real-time correction services
- Patented Z-Blade technology for optimal GNSS performance
 - Full utilization of signals from all 6 GNSS systems (GPS, GLONASS, BeiDou, Galileo, QZSS and SBAS)
 - Enhanced GNSS-centric algorithm: fully-independent GNSS signal tracking and optimal data processing, including GPS-only, GLONASS-only or BeiDou-only solution (autonomous to full RTK)
 - Fast search engine for quick acquisition and re-acquisition of GNSS signals
- Patented SBAS ranging for using SBAS code & carrier observations and orbits in RTK processing
- Patented Strobe™ Correlator for reduced GNSS multi-path
- Up to 10 Hz real-time raw data (code & carrier and position output)
- Supported data formats: ATOM, CMR, CMR+, RTCM 2.1, 2.3, 3.0, 3.1 and 3.2 (including MSM), CMRx and sCMRx (rover only)
- NMEA 0183 messages output

REAL-TIME ACCURACY (RMS)^{1,2}

SBAS (WAAS/EGNOS/MSAS/GA)

Horizontal < 50 cm (19.7 in)
 Vertical < 85 cm (33.5 in)

Real-Time DGPS position

Horizontal 25 cm (9.8 in) + 1 ppm
 Vertical50 cm (19.7 in) + 1 ppm

Real-Time Kinematic position (RTK)

Horizontal8 mm (0.3 in) + 1 ppm
 Vertical15 mm (0.6 in) + 1 ppm

GIS accuracy modes

30/30
 Horizontal30 cm (11.8 in)
 Vertical30 cm (11.8 in)
 7/2 (firmware option needed)
 Horizontal7 cm (2.8 in)
 Vertical 2 cm (0.8 in) GAN

REAL-TIME PERFORMANCE

Instant-RTK® Initialization

- Typically 2 sec for baselines < 20 km
- Up to 99.9% reliability
- RTK initialization range over 40 km (25.0 mi)

POST-PROCESSING ACCURACY (RMS)^{1,2}

Static & Fast static

Horizontal 3 mm (0.1 in) + 0.5 ppm
 Vertical5 mm (0.2 in) + 0.5 ppm

High-Precision Static³

Horizontal 3 mm (0.1 in) + 0.1 ppm
 Vertical35 mm (0.14 in) + 0.4 ppm

Post-Processed Kinematic (PPK)

Horizontal8 mm (0.3 in) + 1 ppm
 Vertical15 mm (0.6 in) + 1 ppm

DATA LOGGING CHARACTERISTICS

Recording interval 0.1 – 999 seconds

PHYSICAL CHARACTERISTICS

Size 21 x 21 x 7 cm (8.3 x 8.3 x 2.3 in)
 Weight 930 g (2.08 lb)

User interface

- Five LEDs for Power, Tracking, Bluetooth, Recording, Radio operations

I/O interface

- RS232 serial link
- USB 2.0/UART and USB OTG
- Bluetooth 2.1 + EDR. Long range Class 1 (17dbm)

Memory

- 256 MB internal memory NAND Flash
- Over a month of 15 sec. raw GNSS data from 14 satellites

Operation

- RTK rover & base
- RTK network rover: VRS, FKP, MAC
- NTRIP, Direct IP
- Post-processing
- Trimble RTX (satellite and cellular/IP)

ENVIRONMENTAL CHARACTERISTICS

Operating temperature –40 °C to +65 °C / (–40 °C to +149 °F)⁴
 Storage temperature –40 °C to +85 °C / (–40 ° to +185 °F)⁵
 Humidity 100% condensing
 IP67 waterproof, sealed against sand and dust
 Drop2 m (6.6 ft) pole drop on concrete
 Shocks MIL STD 810 (fig 516.5-10) (01/2000)
 Vibration MIL-STD-810F (fig 514.5C-17) (01/2000)

Trimble RTX Initialization ^{1, 2, 6}			
	Horizontal (RMS)	Initialization	GNSS
CenterPoint® RTX	< 4 cm	< 30 mins, < 5 mins	L1 + L2
FieldPoint RTX™	< 10 cm	< 15 mins, < 5 mins	L1 + L2
RangePoint® RTX	< 30 cm	< 5 mins	L1 + L2
ViewPoint RTX™	< 50 cm	< 5 mins	L1

- 1 Accuracy and TTFF specifications may be affected by atmospheric conditions, signal multipath, satellite geometry and corrections availability and quality.
- 2 Performance values assume minimum of five satellites, following the procedures recommended in the product manual. High multipath areas, high PDOP values and periods of severe atmospheric conditions may degrade performance.
- 3 Long baselines, long occupations, precise ephemeris used.
- 4 At very high temperatures UHF module should not be used in the transmitter mode. With UHF transmitter on radiating 2W of RF power, the operating temperature is limited to + 55 °C (+131 °F).
- 5 Without batteries. Batteries can be stored up to +70 °C (+158 °F).
- 6 Receiver initialization time varies based on GNSS constellation health, level of multipath, and proximity to obstructions such as large trees and buildings.



Contact your local Trimble Authorized Distribution Partner for more information

NORTH AMERICA
 Trimble Inc.
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE
 Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC
 Trimble Navigation
 Singapore PTE Limited
 3 HarbourFront Place
 #13-02 HarbourFront Tower Two
 Singapore 099254
 SINGAPORE

