



# Trimble Forensics SX12

## SCANNING TOTAL STATION



### KEY FEATURES

The Trimble® SX12 scanning total station is the do it all instrument you need as your go to for any and every scene you respond to. Capable of collecting survey grade point clouds and data points, there is no scene too large or small for the Trimble SX12.

#### Integrated System

- ▶ **Collect** high accuracy survey data and rich point cloud data with Trimble Forensics Capture and the Trimble SX12
- ▶ **Process** all of your evidence with Trimble Forensics Reveal or Trimble Forensics RealWorks® for even more advanced point cloud processing
- ▶ **Present** your evidence to the jury using our free and robust courtroom presentation tool Trimble Forensics ShowCase
- ▶ **Rely** on your equipment for years to come with the Trimble Service and Warranty guarantee

**Learn more:** [forensics.trimble.com/SX12](https://forensics.trimble.com/SX12)

**SURVEY PERFORMANCE**

**Angle measurement**

Sensor type	Absolute encoder with diametrical reading
Angle measurement accuracy <sup>1</sup>	1" (0.3 mgon)
Angle display (least count)	0.1" (0.01 mgon)

**Automatic level compensator**

Type	Centered dual-axis
Accuracy	0.5" (0.15 mgon)
Range	±5.4' (±100 mgon)
Electronic 2-axis level, with a resolution of	0.3" (0.1 mgon)
Circular level in tribrach	8/2 mm

**Distance measurement**

<b>Accuracy</b>		
Prism mode	Standard <sup>2</sup>	1 mm + 1.5 ppm
	Tracking <sup>2,3</sup>	2 mm + 1.5 ppm
DR mode	Standard <sup>2</sup>	2 mm + 1.5 ppm

<b>Measuring time</b>		
Prism mode	Standard	1.6 s
DR mode	Standard	1.2 s

<b>Range</b>		
Prism mode <sup>4</sup>	1 prism	1 m – 5,500 m
DR mode	Kodak White Card (Catalog number E1527795)	1 m – 800 m
	Kodak Grey Card (Catalog number E1527795)	1 m – 450 m

<b>Autolock<sup>®</sup> and Robotic Range</b>		
	Autolock range - traverse 50 mm <sup>5</sup>	1 m – 800 m
	Autolock range - 360 prism	1 m – 300 m <sup>6</sup> / 700 m <sup>5</sup>
	Angle accuracy <sup>1</sup>	1"

**SCANNING PERFORMANCE**

**general scanning specifications**

Scanning principle	Band scanning using rotating prism in telescope
Measurement rate	26.6 kHz
Point spacing	6.25 mm, 12.5 mm, 25 mm or 50 mm @ 50 m
Field-of-view	360° x 300°
Coarse scan; Full Dome - 360° x 300° Density: 1 mrad, 50 mm spacing @ 50 m	Scan time: 12 minutes
Standard scan; Area Scan - 90° x 45° Density: 0.5 mrad, 25 mm spacing @ 50 m	Scan time: 6 minutes

**range measurement**

Range principle	Ultra-high speed time-of-flight powered by Trimble Lightning technology	
Range	Kodak White Card (Catalog number E1527795)	0.9 m – 600 m
	Kodak Gray Card (Catalog number E1527795)	0.9 m – 350 m

<b>Range noise</b>		
	@ 50 m on 18–90% reflectivity	1.5 mm
	@ 120 m on 18–90% reflectivity	1.5 mm
	@ 200 m on 18-90% reflectivity	1.5 mm
	@ 300 m on 18-90% reflectivity	2.5 mm

<b>Scanning Accuracy</b>		
Scanning Angular Accuracy	5" (1.5 mgon)	
3D position Accuracy @ 100 m <sup>7</sup>	2.5 mm	

# Trimble Foresnics SX12 SCANNING TOTAL STATION

## EDM SPECIFICATIONS

Beam divergence DR mode	0.2 mrad
Atmospheric correction	Available through field and office software

## IMAGING PERFORMANCE

Imaging principle	3 calibrated cameras in telescope powered by Trimble VISION™ technology
Cameras total field of view	360° x 300°
Live view frame rate (depending on connection)	Up to 15 fps
File size of one total panorama with overview camera	15 MB – 35 MB

### Panorama Measurement Time and Resolution

Overview Panorama	Full dome 360° x 300° with 10% overlap	2.5 mins, 40 images, 15 mm @ 50 m per pixel
Primary Panorama	Area capture 90° x 45° with 10 % overlap	2.5 mins, 48 images, 3.5 mm @ 50 m per pixel

## CAMERAS SPECIFICATIONS

### General Camera Specifications

Resolution of each camera chip	8.1 MP (3296 x 2472 pix)
File format of images	.jpeg
Field of view max	57.5° (horizontal) x 43.0° (vertical)
Field of view min	0.51° (horizontal) x 0.38° (vertical)
Total zoom (no interpolation)	107 x
35 mm equivalent focal length	36–3850 mm
Exposure modes	Auto, spot exposure
Manual exposure brightness	±5 steps
White balance modes	Auto, daylight, incandescent, overcast
Temperature compensated optics	Yes
Calibrated cameras	Yes

### Overview Camera

Position	Parallel to measurement axis
One pixel corresponds to	15 mm @ 50 m

### Primary Camera

Position	Parallel to measurement axis
One pixel corresponds to	3.5 mm @ 50 m

### Telescope Camera

Position	Coaxial
Focusing	Automatic, manual
Focusing distance	1.7 m to infinity
One pixel corresponds to	0.69 mm @ 50 m
Pointing precision (std dev 1 sigma)	1" (HA: 1.5 cc, VA: 2.7 cc)

### Plummet Camera

Usable range	1.0–2.5 m
Resolution on ground - one pixel corresponds to	0.2 mm @ 1.55 m instrument height
Accuracy	0.5 mm @ 1.55 m instrument height

## GENERAL SPECIFICATIONS

Communication	WiFi, 2.4 Ghz Spread Spectrum, cabled (USB 2.0)
IP-rating	IP55
Operating temperature range	–20 °C to 50 °C
Security	Dual layer password protection



# Trimble Forensics SX12 SCANNING TOTAL STATION

## SYSTEM SPECIFICATIONS

<b>Servo system</b>		
	MagDrive™ servo technology	Integrated servo/angle sensor electromagnetic direct drive
	Clamps and slow motions	Servo-driven
<b>Centering</b>		
	Centering system	Trimble 3-pin
	Plummets	Built-in video plummet
		Split optics tribrach with optical plummet
<b>Power supply</b>		
	Internal battery	Rechargeable Li-Ion battery 11.1 V, 6.5 Ah
<b>Operating time<sup>8</sup></b>		
	One internal battery	Up to 2.25 hours
	Three batteries in multi-battery adapter and one internal	Up to 7 hours
<b>Weight and dimensions</b>		
	Instrument	7.5 kg
	Tribrach	0.7 kg
	Internal battery	0.35 kg
	Trunnion axis height	196 mm
	Front lens aperture	56 mm

- 1 Standard deviation according to ISO17123-3.
- 2 Standard deviation according to ISO17123-4.
- 3 Single measurement, target static.
- 4 Standard clear conditions (No haze, Overcast or moderate sunlight with very light heat shimmer, visibility about 10 km).
- 5 Under perfect conditions (Overcast, visibility about 40 km, no heat shimmer).
- 6 Normal conditions (Moderate sunlight, visibility about 10 km, some heat shimmer).
- 7 Standard deviation of fitted position of a sphere target.
- 8 The capacity in -20 °C is 75% of the capacity at +20 °C.

Specifications subject to change without notice.



Contact your local Trimble Authorized Distribution Partner for more information

**NORTH AMERICA**  
 Trimble Inc.  
 10368 Westmoor Dr  
 Westminster CO 80021  
 USA

**EUROPE**  
 Trimble Germany GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY

**ASIA-PACIFIC**  
 Trimble Navigation  
 Singapore PTE Limited  
 3 HarbourFront Place  
 #13-02 HarbourFront Tower Two  
 Singapore 099254  
 SINGAPORE

